

Hersteller / Flugzeugtyp	Hauptrad	Maße	Bereifung	Schlauch	Bugrad	Maße	Bereifung	Schlauch	Stützrad Spornrad	Maße	Bereifung	Schlauch
PZL Swidnik												
PW 5	Liliput 4"	88-17 #044200	4.00-4 #064491	90° 28G 4.00-4	Laufrad 4"	85-17 #034600	260x85 #064991	90° 32G T87 260x85				
PW 6	Standard 5	125-20 #045400	5.00-5	90°TR67 5.00-5	Laufrad 4"	85-17 #034600	260x85 #064991	90° 32G T87 260x85				
	oder SB 5" Classic Umbau	122-20 #055152	5.00-5	90°TR67 5.00-5								
Rolladen-Schneider (Musterbetreuer: DG-Flugzeugbau)												
LS 1a bis 1f	Liliput 4"	88-17 #044200	4.00-4 #064491	90° 28G 4.00-4								
LS 3	Liliput 4"	88-17 #044200	4.00-4 #064491	90° 28G 4.00-4								
	oder Kobold 4"	103-20 #044300		90° 32G TR87 4.00-4								
	Umbau SB 4" Classic	110-20 #054111										
LS 4	Kobold 4"	103-20 #044300	4.00-4 #064491	90° 32G TR87 4.00-4					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
	Umbau SB 4" Classic	110-20 #054111										
LS 6 / LS 7	Kobold 4"	103-20 #044300	4.00-4 #064491	90° 32G TR87 4.00-4					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
	Umbau SB 4" Classic	110-20 #054111										
LS 8	Kobold 4"	103-20 #044300	4.00-4 #064491	90° 32G TR87 4.00-4					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
	Umbau SB 4" Classic	110-20 #054111										
	Standard 5"	113-20 #045100	5.00-5	90°TR67 5.00-5					#			
Ruschmeyer												
R 90	SB 6" Classic	140-40 #056650	15x600-6	gerade TR20 15x6.00-6	Laufrad 5"	125-30 #035505	5.00-5	90° TR67 5.00-5				
Scheibe (Musterbetreuer: Scheibe Aircraft)												
SF 25 A Motorfalke	Super 6"	154-30 #046100	6.00-6	JS2-Tost #066992					Max	50-20 #033100	200x50 #063191	90° 30° 28G 200x50
SF 25 B Einbein	Super 6"	154-30 #046100	6.00-6	JS2-Tost #066992					Max	50-20 #033100	200x50 #063191	90° 30° 28G 200x50
	Gnom 4"	213-30 #044800	8.00-4 #064791	TR12 8.00-4								
SF 25 C Zweibein SF 36	2x Standard 5"	130-35 #045810	5.00-5	90° TR67 5.00-5					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
SF 25 C Dreibein	2x Standard 5"	130-35 #045810	5.00-5		Laufrad 4"	85-20 #034000	5.00-4 #064391	90° TR67 5.00-4	Max	50-20 #033100	200x50 #063191	90° 30° 28G 200x50
SF 25 E Superfalke	2x Super 6"	154-30 #046100	6.00-6	JS2-Tost #066992					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
SF 28 A Tandem-Falke	Gnom 4"	213-30 #044800	8.00-4 #064791	TR12 8.00-4					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
SF 27	Liliput 4"	88-17 #044200	4.00-4 #064491	90° 28G 4.00-4								
SF 34	Standard 5"	113-20 #045100	5.00-5	90° TR67 5.00-5	Laufrad 4"	85-20 #034000	260x85 #064991	90° 32G T87 260x85	Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
Bergfalke II / III / IV Mü13	Liliput 4"	88-17 #044200	4.00-4 #064491	90° 32G TR87 4.00-4					Max	50-20 #033100	200x50 #063191	90° 30° 28G 250x50
	Kobold 4"	103-20 #044300							Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
Spatz	LR 4"	div.	4.00-4 #064491									
Schempp-Hirth												

Hersteller / Flugzeugtyp	Haupttrad	Maße	Bereifung	Schlauch	Bugrad	Maße	Bereifung	Schlauch	Stützrad Spornrad	Maße	Bereifung	Schlauch
Cirrus /Cirrus VTC Standard-Cirrus/B/G/ G/81 /B Top Std. Cirrus CS 11/75 L ST Std. Cirrus CS 11/78 L ST (Standard) Cirrus K	4" Liliput	88-17 #044200	4.00-4 #064491	90° 28G 4.00-4								
	4" Kobold o. Hydr. Betätigung	113-20 #044400	4.00-4 #064491	90° 39G 4.00-4								
Mini-Nimbus HS7 / B / C	Kobold 4"	113-20 #044400	4.00-4 #064491	90° 39G 4.00-4								
	SB 4" (TM03-2011)	110-20 #054111	4.00-4 #064491	90° 32G TR87 4.00-4								
Discus a / b / 2a / bT / bM / CS Ventus a / b / c / 2a Ventus-bT / cM / cT	Kobold 4"	103-20 #044300	4.00-4 #064491	90° 32G TR87 4.00-4					#		200x50	
	Zulassung für CS in Arbeit SB 4" (TM03-2011)	110-20 #054111										
Discus- 2c / 2 cT / 2c FES Ventus 2c / 2cM / 2cT	SB 5"	109-20 #055188	5.00-5	90° 28G TR87 5.00-5					# oder Mini 150 D "mit Abdeckung"	30-12 #031522	150x30 #062151	30° 60° 25G 150x30
	SB 5" Penta (TM 02/2011)	100-20 #055520										
Discus 2b / 2T Ventus 2b	Kobold 4"	103-20 #044300	4.00-4	90° 32G TR87					#		200x50	
	SB 4" (TM03-2011)	110-20 #054111	#064491	4.00-4								
	SB 5"	109-20 #055188	5.00-5	90° 28G TR87					# oder Mini 150 D "mit Abdeckung"	30-12 #031522	150x30 #062151	30° 60° 25G 150x30
	(nicht Ventus 2b) SB 5" Penta (TM 02/2011)	100-20 #055520		5.00-5								
Janus B / C / Ce / CM / CT	Bimbo 5"	155-30 #045950	380x150	90° TR67 5.00-5	Laufgrad 4"	85-20 #034000	3.00-4 #064891	90° 32G TR87 #064292	#		200x50	
	oder SB 5"	145-30 #055161	380x150 #065681	90° TR67 5.00-5								
Nimbus-2 / 2B / 2C / 2M	Standard 5"	95-20 #045000	5.00-5 / 10 pr #068521	90° 28G TR87 5.00-5								
	oder SB 5"	109-20 #055188 = Ersatz für 105-20										
Nimbus-3 / 3T	Standard 5"	95-20 #045000	5.00-5 / 10 pr #068521	90° 28G TR87 5.00-5								
	oder SB 5"	109-20 #055188 = Ersatz für 105-20										
Nimbus 4 / 4T / 4M	SB 5" Classic	145-30v #055162	380x150	90° TR67 5.00-5					#		200x50	
Nimbus 3D / 3DT / 3DM	SB 5" Classic	145-30v #055162	380x150	90° TR67 5.00-5	Laufgrad 4"	85-20 #034000	3.00-4 #064891	90° 32G TR87 3.00-4	#		200x50	
Duo Discus, C, T Nimbus 4 D / 4DT / 4DM	SB 5" Classic	145-30v #055162	380x150 #065691	90° TR67 5.00-5	Laufgrad 4"	85-20 #034000	3.00-4 #064891	90° 32G TR87 3.00-4	#		200x50 #063191	90° 90° 28G 200x50
	SB 5" Penta (TM 01/2011)	135-30 #055538	380x150 #065691	90° 28G TR87 5.00-5								
Arcus / T / M	SB 5" Penta (TM 01/2011)	135-30 #055538	380x150	90° 28G TR87 5.00-5	Laufgrad 4"	85-20 #034000	3.00-4 #064891	90° 32G TR87 3.00-4	Max II Sonderform	50-12 #033412	200x50 #063191	90° 90° 28G 200x50
Quintus	SB 5" Penta	115-30 #055531	380x150	90° 28G TR87 5.00-5					Max II Sonderform	50-12 #033412	200x50 #063191	90° 90° 28G 200x50
Ventus 3 Sport / 3 Performance	SB 5" Penta	103-20 #055523	336x115 #065221	90° TR87 5.00-5					Mini 150	30-12	150x30 #062151	
									Max II	50-12 #033112	200x50 #063191	90° 90° 28G 200x50

Hersteller / Flugzeugtyp	Hauptrad	Maße	Bereifung	Schlauch	Bugrad	Maße	Bereifung	Schlauch	Stützrad Spornrad	Maße	Bereifung	Schlauch
Schleicher												
Ka 6 / K 8	4" Rad	div.	4.00-4						Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
Ka 7	Standard 5"	125-30 #045430	380x150	90° TR67 5.00-5								
ASK 13	Standard 5"	125-20 #045400	5.00-5	90° TR67 5.00-5	Laufrad 4"	100-17 #034100	4.00-4 #064491	90° 39G 4.00-4	Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
	oder SB 5" Umbau (TM 10 "Schleicher") #051562	109-20 #055188	5.00-5	90° TR87 5.00-7								
ASW 15	Liliput 4"	88-17 #044200	4.00-4 #064491	90° 28G 4.00-4								
	Standard 5"	125-20 #045400	5.00-5	90° TR67 5.00-5								
K 12/ASK 14 / ASK 18	Standard 5"	125-20 #045400	5.00-5	90° TR67 5.00-5								
ASK 16 / ASW 17	Standard 5" (ASK 16 - 2x)	130-35 #045810	5.00-5	90° TR67 5.00-5								
ASW 19/19B / ASW 20	Standard 5"	125-20 #045400	5.00-5	90° TR67 5.00-5					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
	Hydr. Betätigung #045925	125-20	5.00-5	90° TR67 5.00-5								
ASW 20 B / BL / C / CL	Cleveland	40-78B	5.00-5						Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
ASK 21 / 21 Mi	Cleveland	40-78B	5.00-5		Laufrad 4"	100-17 #034100	4.00-4 #064491	90° 39G 4.00-4	Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
	SB 5" Penta (Schleicher TM33 u. TM5)	125-1 1/4" #055572		90° TR87 5.00-5								
ASK-21 B	SB 5" Penta	125-1 1/4" #055572	380x150 #065681	90° TR87 5.00-5	Laufrad 4"	100-17 #034100	4.00-4 #064491	90° 39G 4.00-4	Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
ASW 22	Cleveland	40-78/77	5.00-5						Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
ASK 23	Standard 5"	125-20 #045400	5.00-5	90° TR67 5.00-5	Laufrad 4"	85-17 #034600	260x85 #064991	90° 32G T87 4.00-4	Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
ASH 25	SB 5" Classic	145-30 #055161	380x150 #065681	90° TR67 5.00-5					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
ASW 24 / 24 B / 24 E / 27 / 28	Cleveland	40-78B	5.00-5						Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
ASH 26	Cleveland	40-78B	5.00-5						Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
	SB 5" Penta	125 1 1/4" #055572		90° TR87 5.00-5								
ASG 29 /29 E?	SB 5" Penta	125 1 1/4" #055572	5.00-5	90° TR87 5.00-5					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
ASH 30 Mi	SB 6" Penta	138-30 #056960	15x6.00-6	90° TR87 15x6.00-6					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
ASH 31 Mi	SB 5" Penta	125 1 1/4" #055572	5.00-5 10pr #068521	90° TR87 5.00-5					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
ASG 32 / 32 EI / 32 Mi									Max II	50-12 #033112	200x50 #063191	90° 90° 28G 200x50
	SB 6" Penta	138-30 #056960	15x6.00-6 6pr	90° TR87 15x6.00-6					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
Sportavia (Musterbetreuer: E.I.S.)												
RF 5	Super 6"	154-30 #046100	6.00-6	JS2-Tost #066992					Laufrad 4"	60-20 #034400	2.80/2.50-4 #064591	90° TR87 2.80/2.50-4
	Super 6" auf BS umgebaut	wahrscheinlich!!! 154-30										
	SB 6" Super	151-30 #056161										

Hersteller / Flugzeugtyp	Haupttrad	Maße	Bereifung	Schlauch	Bugrad	Maße	Bereifung	Schlauch	Stützrad Spornrad	Maße	Bereifung	Schlauch
Sportine Aviacija												
LAK 17 a / 19 / 20	Standard 5"	113-20 #045100	5.00-5	90° TR67 5.00-5								
	SB 5" Classic	115-20 #055191	380x150	90° TR67 5.00-5								
Stemme												
S 10 / S 10-V / S 10-VT	2x 5" SB-Standard	127-30 #055212	5.00-5 #065091	90° TR67 5.00-5					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
	2x 5" SB Penta	120-30 #055544	380x150 #065691	90° TR87 5.00-5								
S 12	2x 5" SB Penta	120-30 #055544	380x150 #065691	90° TR87 5.00-5					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
Zakłady Lotnicze Margański & Mysłowski Bielsko												
SWIFT	Standard 5"	115-25 #045255	350x135 #065891	90° TR67 5.00-5					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3
	Umbau 5" SB Classic #051570	115-25 #055192	5.00-5	90° TR67 5.00-5								
FOX	SB 5" Classic	134-30 #055153	5.00-5	90° TR67 5.00-5					Moritz	50-20 #032100	210x65 #062094	90° 28G 2.50-3